

F E C

COMMERCIAL CONTROL VALVES

IDEAL FOR SMALL COMMERCIAL AND INDUSTRIAL APPLICATIONS

OF FOREIGN & DOMESTIC P

FEA E /BE EFI

Lead-free brass valve body for superior strength and durability

Continuous service flow rate of 46 GPM with a backwash of 47 GPM

Backwash capability accommodates softener tanks up to 36" and filters up to 24" in diameter

Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system

Designed for single or multiple tank systems

Environmental protective cover for water resistance, corrosion resistance, and UV stability

Time-tested, hydraulically-balanced piston for service and regeneration

Rugged-built electromechanical timer designed with heavy duty 3/8" wide plastic gears

I

Filter or softener control valves

No hard water bypass piston

Brine cam auxiliary switch

Electromechanical timer auxiliary switch

Hot water

Versatile top or side mount

Manual lever operations

- Network controller uses on-board communication capabilities to link multiple valves (via off-the-shelf CAT3, CAT5, or better cables) for system types 4, 5, 6, 7, 9, and 14
- Large LCD display and user-selectable time clock or metered function; usable for filtration and softener systems

- Offers a two-line, 16 character LCD backlit display for easy entering of master and user programming as well as view of diagnostics

E - Simple to adjust and easy to service with quick access to all internal components



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 61 Section 8 Material Safety Only.



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 372 for Lead Free Compliance.



Restriction of Hazardous Substance Compliant

